



# ECOSIL

**D19**

VERSION: 121212  
Page: 1/2

## WATER-BASED BRUSHABLE SEAM SEALER

### DEFINITION

**ECOSIL** is a water-based sealant for use in the bodywork sector, based on elastomers. Because of its low volatile organic content, it is an environmentally healthy product.

It has been specially developed to possess the necessary properties for application with brushes. It does not fall off, or form threads, and it spreads easily. Due to the evolution of its drying, it permits to correct the application during 5 minutes. To facilitate work, a brush is supplied with every pot of **ECOSIL**.



Its flexibility makes it ideal for use in sealing all bodywork joints, and in boots, wheel arches, etc. Once it is completely dry, **ECOSIL** acquires a perfect adherence on many surfaces.

Its colour, which is similar to the colour of the majority of sealants of origin, changes during the drying and permits us to follow the evolution of it. **ECOSIL** can be painted over with any enamel for bodywork, both water based and solvent based enamels.


### PHYSICAL CHARACTERISTICS

<b>Nature:</b>	Elastomers
<b>Colour:</b>	Grey
<b>Specific weight:</b>	1,3 kg/l at 20°C
<b>VOC:</b>	40 g/l
<b>Solid content:</b>	70 %

### APPLICATION

	<b>DA93</b>
	<i>Apply with brush imitating the finishing of origin.</i>

### DRYING TIMES

	T <sup>e</sup> (C)	R.H. (%)	Dry film thickness (mm)	
ECOSIL	23	60	0,5	1h
	23	60	4	4h

### REMARKS

The drying depends on the thickness, the ventilation, the environmental temperature and the relative humidity.

### EQUIPMENT CLEANING

Use preferably warm water. If the product is dry use acetone.

### SAFETY

Follow instructions of product label. For more information check the Safety Data Sheet. Compliant with the National Statutory Regulation for Health and Safety at Work and Waste Disposal.

### STORAGE

Store the product in a ventilated place far from direct exposure to sunlight. Keep between +5°C and +30°C.

### GUARANTEE

In unopened original packaging, one year from manufacturing date.

For any technical information contact with our Customer Attention Service or our Technical Department.  
ROBERLO SA declines any responsibility due to an incorrect use of the product.